

# Produktdatenblatt



## ECO Uni-Clean

Powerful cleaner for the removal of oil, grease, and heavy soiling of all kinds. Ideal for use in commercial kitchens, industrial facilities, workshops, and similar environments. Designed for effortless cleaning of walls, ventilation systems, machinery, and floors. Suitable for both machine application and manual cleaning.

### Areas of Application

Suitable for all washable surfaces and floor coverings, including:

- PVC, Natural and artificial stone, Tiles, Taps and fittings, Sanitary porcelain
- Chrome, Stainless steel

Recommended for use in industry, manufacturing plants, workshops, garages, and commercial kitchens. Also suitable for cleaning machinery, machine parts, tools, and protective covers.

### Dosage

#### Normal soiling:

10–200 ml per 10 litres of water (0.1–2%)

#### Heavy soiling:

500 ml–2 litres per 10 litres of water (5–20%)

### Application Instructions

#### Normal soiling:

Apply the cleaning solution, scrub the surface, then vacuum or remove the dirty solution.

#### Heavy soiling:

Apply the cleaning solution (if required using a sponge holder or applicator), allow to act for 15–30 minutes, scrub mechanically, then vacuum up the solution. Rinse if necessary.

#### Machinery and tool parts:

Wash the surface thoroughly and rinse. If required, wipe dry with a wrung-out cloth.

### Special Notes

Wastewater contaminated with hydrocarbons should be discharged through an oil separator. Follow the recommended dosage instructions. Correct dosing reduces water consumption and water pollution.

Dispose of contents/container in accordance with local, regional, national, and international regulations.

The manufacturer accepts no liability for damage resulting from improper use.

### Technical Data

Shelf life: At least 2 years

pH value: Concentrate: 12 / 1% solution: 9

### Ingredients:

Anionic surfactants, soap, non-ionic surfactants, fragrances, water.